



VpCI® METALWORKING PRODUCTS



VpCI®-326



PRODUCT DESCRIPTION

VpCI®-326 is a corrosion inhibitor oil additive for hydraulic oil and gearbox assemblies. It performs effectively under adverse conditions and in the presence of such corrosive species as chlorides, sulfur compounds, or hydrogen sulfide. VpCI®-326 contains no hazardous chromates, nitrites, or phosphate inhibitors.

VpCI®-326 utilizes the finest paraffinic petroleum distillates as carriers. VpCI®-326 possesses an exceedingly high flash point, enhancing in-plant safety when compared to common oil protectants.

VpCI®-326 is supplied in concentrate form, which is easily diluted with lubricating, hydraulic, or preservative oils; saving shipping and inventory expense.

VpCI®-326 is a broad range corrosion inhibitor not only effective on ferrous metals, but also effective on zinc, aluminum, galvanized steel, copper, cadmium, silver, brass, and many other alloys.

FEATURES

- Provides universal corrosion protection to ferrous and non-ferrous metals
- Nitrite-free, and thermally stable, providing long-lasting contact and vapor phase corrosion protection
- With VpCI®-326, most lubricants can be upgraded in their anti-corrosion ability providing continuous corrosion protection during standby and shutdown periods

- NATO 6850-66-132-6100
- NSN 6850-01-470-3358

TYPICAL APPLICATION

Fog interiors with VpCI®-326 concentrate at 1 liter/m³ (1 oz/ft³) of enclosed space.

VpCI®-326 should not be used in applications with the potential to encounter liquid water. Contact Cortec® for application questions.

TYPICAL PROPERTIES

Oil Characteristics		Typical Values
Appearance		Clear Yellow Color
Specific Gravity		0.88
Viscosity (ASTM D92)	40 °C	19.2 cSt
	100 °C	3.6 cSt
	Index	48
Pour Point (ASTM D6749)		-36 °C (-33 °F)
Flash Point (ASTM D92)		138 °C (280 °F)
Fire Point (ASTM D92)		140 °C (284 °F)
Total Acid Number (ASTM D974)	mg KOH/g	52.2
ISO Particle Count Code		17/15/12
Oil Separability (ASTM D1401) @ 54 °C (129 °F)	Oil, ml	0
	Water, ml	0
	Emulsion, ml	80
	Time, min	60
Foaming Characteristics (ASTM D892)	Seq. I	20/0/12
	Seq. II	25/0/7
	Seq. III	5/0/3

Properties listed above are typical of those obtained through normal production and do not constitute a specification. VpCI®-326 is generally soluble in hydrocarbon based fluids, however compatibility and solubility should be verified prior to use. Please contact Cortec® Technical Service for more information.



PACKAGING AND STORAGE

VpCl®-326 is available in 32 oz. (0.92L) containers, 5 gallon (19 liter) pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk.

**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 01/12/17. Supersedes: 06/10/15. ©Cortec Corporation 2002-2013 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2013, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.